



Features & Benefits

1	Four(4) external 3.5-inch hot-swap HDD supported (SAS/SATA backplane with Vitesse VSC410 enclosure management controller chip (SEP) on board)
2	LED for hard drive status - solid blue for power & blinking blue for activity
3	LED for hard drive status - solid red for failure
4	System reset
5	LED for system power, over temperature, and fan failure
6	RS232 port for firmware update (SES2 & SAF-TE protocol or SFF8448 SGPIO/TWS support)
7	One(1) SFF8087 mini-SAS 4x connector
8	1x 80mm self-contained cooling fan

Model Number : XC-34D-2	
Order Information : XC-34D-2	
Materials : Heavy-duty preplated SPGC cold-rolled steel	
Finish :	Zinc-plated with bright chromate
Dimensions :	mm : 128 x 228.4 x 146
W x D x H	inches : 5 x 9 x 5.8
Cooling :	Rear : 1 x 80x25mm fan
Control : System mute	
Indicators : Power, temperature, fan and HDD LED's	

Drive Bay:	3.5" hot-swap	4
Temperature :	0°C(32°F) ~ 50°C(122°F)	
Humidity :	5%~95% non-condensing	
Net Weight :	5kgs / 11lbs	
Cubic Feet :	0.6	
Packaging Dimension (W x D x H) :	mm : 240 x 300 x 230	
Backplane :	SA1P	Description
		SAS 3.0 (SEP)

Mechanical Drawing

